

# ARAZZO / LANA

## SPECIFICATION SHEET

|                             |  |                         |
|-----------------------------|--|-------------------------|
| <b>PRODUCT NAME</b>         | STEEL TYPE II  |                         |
| <b>WEIGHT AND THICKNESS</b> | Weight: 457g / MQ<br>Thickness: 0.432mm to 0.686 mm  |                         |
| <b>TYPE II CRITERIA</b>     | Passes all Criteria for WA 101 TYPE II properties including:<br>Break Strength                      Tear Strength                      Cold Crack<br>Shrinkage                              Stain resistance                      Blocking<br>Coating Adhesion                      Crocking                              Washability<br>Colorfastness                              Heat Aging                              Scrubability                     |                         |
| <b>SPECIFICATIONS</b>       | CCC-408-0 Type II<br>Polyester/vinyl face with non-woven backing<br>WA-101, NSF/ANSI 342 Sustainability Standard<br>NFPA Life Safety Code 101*      Passed Class A   |                         |
| <b>FIRE TESTING RATE</b>    | EU Class Flame (EN15102)   | Passed Class B, s2, d0  |
|                             | ASTM-E84 Tunnel Test   | Passed Class A          |
|                             | CAN/ULC-S102   | Passed all requirements |
|                             | BS476 Parts 6&7  | Passed all requirements |
| <b>MOLD/MILDEW</b>          | ASTM-G21 Specifications  | Passed all requirements |
| <b>SUSTAINABILITY</b>       | NSF – 342 Certified for Silver compliance for all 20 oz. wallcoverings constructions<br>HPD – Health Product Declaration available<br>EPD – Environmental product Declaration available<br>Meets or exceed EU toxicity standards 12149 A,B,C, for heavy metals and formaldehyde<br>Phthalate free formulation<br>Manufactured without the use of Brominated flame retardant<br>*Meets or exceed requirements for flame spread, smoke developed and flashover |                         |