

# PINE NEEDLES / AUTUMN

## SPECIFICATION SHEET

<b>PRODUCT NAME</b>	STEEL TYPE II	
<b>WEIGHT AND THICKNESS</b>	Weight: 457g / MQ Thickness: 0.432mm to 0.686 mm	
<b>TYPE II CRITERIA</b>	Passes all Criteria for WA 101 TYPE II properties including: Break Strength                      Tear Strength                      Cold Crack Shrinkage                              Stain resistance                      Blocking Coating Adhesion                      Crocking                              Washability Colorfastness                          Heat Aging                              Scrubability	
<b>SPECIFICATIONS</b>	CCC-408-0 Type II Polyester/vinyl face with non-woven backing WA-101, NSF/ANSI 342 Sustainability Standard NFPA Life Safety Code 101*      Passed Class A	
<b>FIRE TESTING RATE</b>	EU Class Flame (EN15102)	Passed Class B, s2, d0
	ASTM-E84 Tunnel Test	Passed Class A
	CAN/ULC-S102	Passed all requirements
	BS476 Parts 6&7	Passed all requirements
<b>MOLD/MILDEW</b>	ASTM-G21 Specifications	Passed all requirements
<b>SUSTAINABILITY</b>	NSF – 342 Certified for Silver compliance for all 20 oz. wallcoverings constructions HPD – Health Product Declaration available EPD – Environmental product Declaration available Meets or exceed EU toxicity standards 12149 A,B,C, for heavy metals and formaldehyde Phthalate free formulation Manufactured without the use of Brominated flame retardant *Meets or exceed requirements for flame spread, smoke developed and flashover	