

# PINE NEEDLES / RIKYU

## SPECIFICATION SHEET

<b>PRODUCT NAME</b>	STEEL TYPE II
<b>WEIGHT AND THICKNESS</b>	Weight: 457g / MQ Thickness: 0.432mm to 0.686 mm
<b>TYPE II CRITERIA</b>	Passes all Criteria for WA 101 TYPE II properties including: Break Strength            Tear Strength            Cold Crack Shrinkage                 Stain resistance         Blocking Coating Adhesion         Crocking                 Washability Colorfastness             Heat Aging               Scrubability
<b>SPECIFICATIONS</b>	CCC-408-0 Type II Polyester/vinyl face with non-woven backing WA-101, NSF/ANSI 342 Sustainability Standard NFPA Life Safety Code 101*    Passed Class A
<b>FIRE TESTING RATE</b>	EU Class Flame (EN15102)        Passed Class B, s2, d0 ASTM-E84 Tunnel Test            Passed Class A CAN/ULC-S102                    Passed all requirements BS476 Parts 6&7                 Passed all requirements
<b>MOLD/MILDEW</b>	ASTM-G21 Specifications         Passed all requirements
<b>SUSTAINABILITY</b>	NSF – 342 Certified for Silver compliance for all 20 oz. wallcoverings constructions HPD – Health Product Declaration available EPD – Environmental product Declaration available Meets or exceed EU toxicity standards 12149 A,B,C, for heavy metals and formaldehyde Phthalate free formulation Manufactured without the use of Brominated flame retardant *Meets or exceed requirements for flame spread, smoke developed and flashover